

# Declaration of Performance

No. 007DOP-C-20130701

**1. Unique identification code of the product-type:**

Access profiles, Connect Recessed and Inline profiles (Fire class A1 Durability Class B)

**2. Element allowing identification of the construction product:**

Access Universal profile  
Access Carrier profile  
Access Double carrier profile  
Access Cable channel profile  
Access Transition profile  
Connect Recessed profile Plus  
Connect Recessed profile  
Connect Inline carrier

**3. Intended use (according harmonized technical specification):**

Suspended ceiling substructure component for use internally in buildings

**4. Name, registered trade name and contact address of the manufacturer:**

Saint-Gobain Ecophon AB  
Box 500  
265 03 Hyllinge, Sweden  
[www.ecophon.com](http://www.ecophon.com)

**5. Name and contact address of the authorized representative:**

Not applicable

**6. System(s) of Assessment and Verification of Constancy of Performance of the construction product:**

System 4

**7. Case a construction product covered by a harmonised standard:**

Not applicable

**8. Case of a construction product for which a European Technical Assessment has been issued:**

Not applicable

## Declaration of Performance – Connect T24 grid (cont.)

### 9. Declared performance:

All characteristics listed in the table hereunder are determined in harmonized standard EN 13964:2004 – Suspended ceilings – Requirements and test methods.

Product type	Essential characteristics	Performance
Access Universal profile	Service load, span=1800 mm, Class 1	140 N
Access Carrier profile	Service load, span=1800 mm, Class 1	140 N
Access Double carrier profile	Service load, span=1800 mm, Class 1	140 N
Access Cable channel profile	Service load, span=1800 mm, Class 1	140 N
Access Transition profile	Service load, span=1800 mm, Class 1	140 N
Connect Recessed profile Plus	Service load, span=400 mm, Class 1	1210 N
Connect Recessed profile	N/A	n.p.d
Connect Inline carrier	Service load, span=1000 mm, Class 1	23 N

All products conform to:      Reaction to fire: Euroclass A1  
Durability:                              Corrosion protection according to EN 13964, Class B

### 10. The performance of the products identified in points no.1 and no.2 is in conformity with the declared performance in point 9.

**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**



Saint Gobain Ecophon AB  
Martin Tykesson  
Product Engineer Grids, Accessories & Lighting  
martin.tykesson@ecophon.se

