

# Declaration of Performance

No. 004DOP-C-20130701

**1. Unique identification code of the product-type:**

Connect Trims (Fire class A1, Durability Class B)

**2. Element allowing identification of the construction product:**

Connect Angle trim  
Connect Angle trim 15/22  
Connect Baffle trim  
Connect Distance trim  
Connect Column trim  
Connect Shadow-line trim  
Connect Frieze trim  
Connect Channel trim  
Connect Channel trim HD  
Connect Flexible wall trim  
Connect Shadow channel trim  
Connect Cover trim  
Connect Modular wall trim

**3. Intended use (according harmonized technical specification):**

Suspended ceiling substructure component for use internally in buildings

**4. Name, registered trade name and contact address of the manufacturer:**

Saint-Gobain Ecophon AB  
Box 500  
265 03 Hyllinge, Sweden  
[www.ecophon.com](http://www.ecophon.com)

**5. Name and contact address of the authorized representative:**

Not applicable

**6. System(s) of Assessment and Verification of Constancy of Performance of the construction product:**

System 4

**7. Case a construction product covered by a harmonised standard:**

Not applicable

**8. Case of a construction product for which a European Technical Assessment has been issued:**

Not applicable

## Declaration of Performance – Connect T24 grid (cont.)

### 9. Declared performance:

All characteristics listed in the table hereunder are determined in harmonized standard EN 13964:2004 – Suspended ceilings – Requirements and test methods.

Product type	Essential characteristics	Performance
Connect Angle trim	Service load, span=200 mm, Class 1	70 N
Connect Angle trim 15/22	Service load, span=200 mm, Class 1	70 N
Connect Baffle trim	Service load, span=1200 mm, Class 1	22 N
Connect Distance trim	Service load, span=200 mm, Class 1	70 N
Connect Column trim	Service load, span=200 mm, Class 1	20 N
Connect Shadow-line trim	Service load, span=200 mm, Class 1	70 N
Connect Frieze trim	Service load, span=200 mm, Class 1	70 N
Connect Channel trim	Service load, span=1200 mm, Class 1	15 N
Connect Channel trim HD	Service load, span=1200 mm, Class 1	15 N
Connect Flexible wall trim	Service load, span=1200 mm, Class 1	15 N
Connect Shadow channel trim	Service load, span=1200 mm, Class 1	100 N
Connect Cover trim	N/A	n.p.d
Connect Modular wall trim	Service load, span=200 mm, Class 1	70 N

All products conform to: Reaction to fire: Euroclass A1  
Durability: Corrosion protection according to EN 13964, Class B

### 10. The performance of the products identified in points no.1 and no.2 is in conformity with the declared performance in point 9.

**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**



Saint Gobain Ecophon AB  
Martin Tykesson  
Product Engineer Grids, Accessories & Lighting  
martin.tykesson@ecophon.se

