

Rigips PRO MIX FINISH



Product Description

PRO MIX FINISH is a fine, ready-mix wall finishing for internal use. Air drying. Suitable for a wide variation of backgrounds as e.g. plasterboards, plasters and concrete.

Advantages

PRO MIX FINISH is a high quality finishing, easy to apply, easy to sand, excellent bond.

Application

PRO MIX FINISH can be used directly from the bucket or with some mixing before use. Clean water could be added if it's necessary. Excessive dilution increases shrinkage and retards drying. Add water in increments to avoid over-thinning. It is recommended that not more than 1 litre be added per 25 kg bucket. If liquid and compound have separated, remix before use.

PRO MIX FINISH can be used as finisher on top of all type of joint fillers. For sanding it is recommended to use a 220 paper when manual and a 120 paper with a machine. A primer (Rikombi-Grund) is recommended prior to a wallpaper application.

PRO MIX FINISH can be used by hand and by Airless application.

Application thickness is up to about 2 mm.

The drying time (overnight) depends on climatic conditions. Do not mix with other materials. Cleaning with clean water.

Site Conditions

Air-, material and background temperature have to be above +8 °C. The background has to be solid, clean, dust free and dry.

Handling

Q3: Cover full surface by thin strength of coating and that followed remove material to close the pores.
Q4: Cover full surface with up to 2mm strength of coating.

Quality Standard

Q3 – Q4

Product Data

Working-time	max. 3 months
Drying time	app. 18 hours
Application-thickness	up to 2 mm
Consumption	Joint-Surface: app. 80 g/m ² Surface: app. 1,7 kg/m ² /mm
Fire resistance	A1
Vapour diffusion resistance	$\mu = 10$
Flexural- and tensile bond strength	According to EN 13963
Package-size	5 kg / 15 kg / 25 kg
Storage: Shelf life: Ensure stock rotation and use within 12 months of the marked date. Protect from freezing - store between +2 °C and +30 °C.	

For further information please contact:

Saint-Gobain Rigips Austria GesmbH
Wiener Neustädter Straße 63
A-2734 Puchberg / Schneeberg

Tel. +43 (0) 2636 / 2203-0
Fax +43 (0) 2636 / 2206-625

www.rigips.com

Indoor 	Manual / Machine 	app. 3 month 	Up to 2 mm 	ca. 1,7 kg/m ² /mm 	Q3-Q4
Application	Handling	Working time	Application thickness	Consumption	Quality standard

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.