

Declaration of Performance

DoP №: ULTRASTIL HYDROPROFIL/2013/1

1. Unique identification code of the product-type: Rigidized metal profiles ULTRASTIL[®] Hydroprofil
2. Element allowing identification of the construction product:
 - name - CD 60 ULTRASTIL[®] Hydroprofil, UD 30 ULTRASTIL[®] Hydroprofil, CW 50 ULTRASTIL[®] Hydroprofil, CW 75 ULTRASTIL[®] Hydroprofil, CW 100 ULTRASTIL[®] Hydroprofil, UW 50 ULTRASTIL[®] Hydroprofil, UW 75 ULTRASTIL[®] Hydroprofil, UW 100 ULTRASTIL[®] Hydroprofil
 - production date on each piece of profile - DD-MM-YYYY
3. Intended use: in building construction, to build try wall interior constructions: partition wall, wall linings, ceilings, attic constructions and others – decorative and of declared acoustic insulation, fire resistance class, reaction on fire and fire spreading.
4. Manufacturer: Budmat Bogdan Więcek, Otolińska Street 25, 09-407 Płock
Production plant: Otolińska Street 25, 09-407 Płock
5. Authorized representative: N/A
6. System of assessment and verification of constancy of performance: System 4
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
PN-EN 14195:2006 Metal framing components for gypsum plasterboard systems. Definitions, requirements and test methods.
8. European Technical Assessment (ETA): N/A
9. Declared performance:

Essential characteristics	Performance							
	C 60 27/60/27	U 27 27/29,2/27	C 50 51/48,8/48	C 75 51/73,8/48	C 100 51/98,8/48	U 50 40/51/40	U 75 40/76/40	U 100 40/101/40
Name acc. to Standard	C 60 27/60/27	U 27 27/29,2/27	C 50 51/48,8/48	C 75 51/73,8/48	C 100 51/98,8/48	U 50 40/51/40	U 75 40/76/40	U 100 40/101/40
Commercial Name	CD 60 ULTRASTIL HYDROPROFIL	UD 30 ULTRASTIL HYDROPROFIL	CW 50 ULTRASTIL HYDROPROFIL	CW 75 ULTRASTIL HYDROPROFIL	CW 100 ULTRASTIL HYDROPROFIL	UW 50 ULTRASTIL HYDROPROFIL	UW 75 ULTRASTIL HYDROPROFIL	UW 100 ULTRASTIL HYDROPROFIL
Reaction to fire	A1 Class							
Tensile strength	180 N/mm ²							
Material	DX51D							
Sheet thickness [mm]	0,55	0,55	0,60	0,60	0,60	0,55	0,55	0,55
Dimensions [mm]	27/60/27	27/29,2/27	51/48,8/48	51/73,8/48	51/98,8/48	40/51/40	40/76/40	40/101/40
Coating type [g/m ²]	Z275							
Harmonized technical specification	PN-EN 14195:2006							

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. A Factory production control system adapted to PN-EN 14195:2006 is established to ensure that the products conform to the stated performance characteristics.

Signed for and on behalf of the manufacturer by:

Andrzej Marciniak, Production Manager

(name and function)

Płock, 01.07.2013

(place and date of issue)

(signature)



Andrzej Marciniak
Kierownik Oddziału Prototypowania Blach