

## Declaration of performance

No. 0615-CPR-222984G-FBR-2013/07/01

1. Unique identification code of the product-type:
  - A. ISOVER REK-31, ISOVER Sauna
  - B. ISOVER KT-40-AL
  - C. KT-37-PAP
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
*See product labels.*
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:  
*Thermal insulation for buildings*
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
*Saint-Gobain Rakennustuotteet Oy, ISOVER  
P.O Box 250  
FI-05801 Hyvinkää  
Finland  
[www.isover.fi](http://www.isover.fi)*
5. Name and contact address of the authorized representative:  
*Not applicable*
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
*AVCP System 1 for Reaction to fire  
AVCP System 3 for other characteristics*
7. Case a construction product covered by a harmonized standard:  
*Bureau Veritas Certification (Notified Body No. 0615)  
performed the determination of the product-type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of factory production control; continuous surveillance, assessment and evaluation of factory production control ; under system 1  
and issued a certificate of constancy of performance.*  
  
*Notified testing laboratory performed also all relevant test reports for other declared characteristics according to harmonized standard.*
8. Case of a construction product for which a European Technical Assessment has been issued:  
*Not applicable*

## 9. Declared performance:

All characteristics listed in the table hereunder are determined in harmonized standard **EN 13162:2012**

Essential characteristics		Performance		
		A	B	C
Reaction to fire - Euroclass Characteristics	Euroclass Characteristics	A2-s1, d0		F
Release of dangerous substances to the indoor environment	Release of dangerous substances	(a)		
Acoustic absorption index	Sound absorption	NPD		
Impact noise transmission index ( <i>for floors</i> )	Dynamic stiffness	NPD		
	Thickness, $d_L$	NPD		
	Compressibility	NPD		
	Air flow resistivity	NPD		
Direct airborne sound insulation index	Air flow resistivity	NPD		
Continuous glowing combustion	Continuous glowing combustion	(b)		
Thermal resistance	Thermal resistance and thermal conductivity	$\lambda_D = 0,031$ W/mK $R_D = 0,80 - 3,20$ m <sup>2</sup> K/W (thickness range 25-100 mm)	$\lambda_D = 0,040$ W/mK $R_D = 1,25 - 2,50$ m <sup>2</sup> K/W (thickness range 50-100 mm)	$\lambda_D = 0,037$ W/mK $R_D = 1,35 - 2,70$ m <sup>2</sup> K/W (thickness range 50-100 mm)
	Thickness	T4	T2	T1
Water permeability	Water absorption, short term	WS	NPD	
	Water absorption, long term	WL(P)	NPD	
Water vapour permeability	Water vapour transmission	Z(1000)		NPD
Compressive strength	Compressive stress or compressive strength	NPD		
	Point load	NPD		
Durability of reaction to fire against	Durability	A2-s1, d0		F

heat, weathering, ageing/degradation	characteristics			
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	$\lambda_D = 0,031$ W/mK $R_D = 0,80 - 3,20$ m <sup>2</sup> K/W (thickness range 25-100 mm)	$\lambda_D = 0,040$ W/mK $R_D = 1,25 - 2,50$ m <sup>2</sup> K/W (thickness range 50-100 mm)	$\lambda_D = 0,037$ W/mK $R_D = 1,35 - 2,70$ m <sup>2</sup> K/W (thickness range 50-100 mm)
	Durability characteristics	(e)		
Tensile/Flexural strength	Tensile strength perpendicular to faces (f)	NPD		
Durability of compressive strength against ageing/degradation	Compressive creep	NPD		

NPD = No performance determined

- (a) European test methods are under development.
- (b) A test method is under development and the standard will be amended when this is available.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Jussi Jokinen, Development manager ISOVER, Saint-Gobain Rakennustuotteet Oy

Hyvinkää 1.7.2013

